

SUPER 500

SUPER 500: the new standard in turf maintenance
- Sweeping - Verticutting - Fail-type mowing - High-level dumping

The SUPER 500 is compact rugged, and multi-talented. Park grounds, recreational areas, extensively maintained areas, ecological meadows, sport grounds, and golf courses are its "home turf". Whether it's sweeping, verticutting, mowing, or collecting grass and leaves, you will be impressed by the SUPER 500 from the first cut in spring until autumn.



TECHNICAL DATA

SUPER 500

Model:	Brush sweeper head	Multi-purpose sweeper head
Function:	Brush sweeper head with parallelogram guiding system	Multi-purpose sweeper head with parallelogram guiding system
Sweeping:	Yes	Yes
Verticutting:	No	Yes (spacing 19/38/57 mm)
Flail mowing:	No	Yes
Anti scalp roller:	Yes (optional)	Centred, height adjustable
Implement change:	-	Yes (no tools required)
Working width in cm:	160	160
Volume capacity in cubic metres:	2,5	2,5
Dumping (hydraulic):	210	210
Working height adjustment:	Slotted spacer rings (adjustment range 15 cm)	
Drawbar:	Clevis swinging drawbar	
Drive:	PTO shaft 540 RPM	PTO shaft 540 RPM
Minimum power requirement for tractor:	11 kW / 15 HP	22 kW / 30 HP
Working roller:	Dual V ribbed belt, automatic tensioning	V ribbed belt drive (10 PL), automatic tensioning
Front tyres:	2 x (11 x 4.00-5)	2 x (11 x 7-4)
Rear tyres:	2 x (23 x 10.50)	2 x (23 x 10.50)
Pendulum carriage:	optional 4 x (18 x 8.50)	optional 4 x (18 x 8.50)
Machine length in cm:	316	316
Machine width in cm:	193	207
Machine height in cm:	177	177
Tare weight in kg (approx.):	900	1000
Gross vehicle weight in kg (approx.):	1400	1400
Maximum drawbar load in kg:	180	180
Golf course kit (optional):	No	Height adjustable sensing roller with wiper and side anti scalp rollers
Electromagnetic remote control:	optional	optional
Lighting:	optional	optional

Descriptions and illustrations are non-binding. We reserve the right to modify the construction and design.